Questions about wheel alignment

What is an alignment?

Wheel alignment is very important to your vehicle. If you hit a pothole or a curb, this may affect the alignment settings of the vehicle.

How often should I have my car aligned?

As a rule, this should be done every 10,000 miles or at least once a year. Depending on how the vehicle is driven.

Why is my steering wheel off centre?

This is due to the front or rear toe being unsymmetrical and in need of adjustment.

My car is pulling to the left or right?

This can be down to the tyres or unequal caster settings.

Does having worn tyres mean that the car can be aligned or do new tyres need to be fitted?

New or old tyre fitted will make no difference to the alignment readings. They will however have an effect on the way the car feels, even after the alignment has been corrected.

Supertracker is the UK's established manufacturer of wheel alignment equipment

Since the 1980's Supertracker have worked along side car and tyre manufactures to bring advanced wheel alignment equipment and training to the local alignment experts, as well as the main dealer garages. This has helped to guarantee that your local Supertracker user is an expert on the most technical subject in the motor trade.

There is a very finely balanced suspension system between you and the road, which can be fully adjusted with precision equipment and advanced on going training. As vehicles evolve we evolve parallel to them in order to keep it that way.





GT House, Ashley Crescent, Sholing, Southampton, SO19 9NA Email: info@supertracker.com

Tel: 02380 443325









Why Four Wheel Alignment?

Reduced Tyre Wear

Tyre wear is a problem if improper alignment has been carried out and mechanical replacement has occurred. A properly aligned vehicle can add thousands of miles to your tyre life. Majority of tyres are replaced due to wear and tear.

Increase Fuel Economy

Fuel mileage increases as rolling resistance decreases. With all four wheels aligned to Supertracker specification you will have the best possible rolling resistance on your vehicle. This will give you the best possibility to reduce fuel consumption.

Correct Handling

If your car pulls left or right, drifts to one side, feels non-responsive in corners, wanders or tramlines when driving on a straight road, these are all symptoms of mis-alignment. This can be corrected and make the vehicle handle properly, making it safer to drive.

Component Inspection

In the alignment process all steering and suspension joints are inspected. Any worn parts can be identified. Parts can be replaced earlier helping to eliminate potential break downs or component failures.

Safer Driving

A suspension system inspection is part of the alignment procedure. This allows worn parts to be detected before they cause costly problems.

The major alignment parameters on a car are:

Camber: What is it?

Camber increases or decreases the tyre's grip on the road by the wheel not being upright, when viewed from the front or rear. Correct camber is a requirement and incorrectly set at best will cause tyre wear but at worse could seriously compromise the overall handling characteristics of the car, making it dangerous.

Caster: What is it?

Caster is the forward or rearward tilt of the steering axis, in reference to the vertical when viewed from the vehicle side. Positive caster is where the steering axis is sloped towards the rear. Negative caster (not common) is where the steering axis is sloped towards the front

Toe: What is it?

Positive Toe is the leading edge of the wheels closer together. Negative Toe is the leading edge of the wheels further apart. Our advice would be not to refer to toe as toe-in. For example negative toe-in is toe out! Better to simply say the car has negative toe or is toed out

The rear wheels on many modern vehicles are just as adjustable as the front.

Suspension:

Suspension misalignment increases tyre wear and can seriously affect vehicle handling. Suspension misalignment costs you money, as well as affecting the way your car handles!

Keep track of your tyre pressure

	441 - 12-3
Registration:	
Make:	
Model:	11 11111
Colour:	A THE NAME OF THE PARTY OF THE
	A SHAW
Tyre Size (Front)	Tyre Size (Rear)
Front Tyre Pressure	Rear Tyre Pressure
	7 7 1
Wheel misalignment of 2mm	
	→
Line of travel taken by car forcing	
misaligned tyre to	
go straight	
Angle of travel	
taken by misaligned	
tyre if allowed to run free of the car	
1100 OF LIFE OUT	